



Short Reference Card

<http://www.python.org>
<http://rgruet.free.fr/PQR2.2.html>

formatting from original source :
<http://www.yukoncollege.yk.ca/%7Ettopper/COMP118/rCheatSheet.html>

http://notebind.com/usr-pdf/python_src.pdf

Contents

[Arithmetic](#) · [Strings](#) · [Assignment](#) · [print](#) · [Getting Input](#) · [if](#) · [while](#) · [Play again?](#) · [Lists](#) · [Text file processing](#) · [Dictionaries](#)

Arithmetic

Constants (Number types):

- integers, e.g. 18, -341. A suffix L indicates a long integer, e.g. 34251673L.
- floating point values, e.g. 3.001

Operations:

- + for addition
- - for subtraction
- * for multiplication
- / for division (watch for integer division, e.g. 19 / 4 = 4, not 4.75)
- % for remainder or modulo, e.g. 19 % 4 = 3
- ** for exponentiation, e.g. 2 ** 4 = 16

Strings

Constants: "This is a string"

Operations:

- = for assignment, e.g. `name = "Tim Topper"`
- + for concatenation, e.g. `"Hi" + "Ho" --> "HiHo"`
- * for repetition, e.g. `3 * "Ho" --> "HoHoHo"`

Notes:

- Strings can be delimited by either double quotes "Tim" or single quotes 'Tim'.
- Multiline values can be assigned to a string by triple quoting the contents, e.g.

```
silly = """Two
Lines"""
```

Trying the same thing without triple quoting results in an error, e.g.

```
silly = "Two
Lines"
```

- Another method is to embed control codes for newline characters into the string, e.g.
`silly = "Two\nLines"`
- The most common control codes are: `\n` for newline and `\t` for tab. The Python Quick Reference provides a complete list.

Like lists Python strings are a sequence type so many list commands also work with strings.

- e.g. `s[i]` accesses element number `i` of the string `s`.

Testing string contents:

- `s.isalnum()`
- `s.isalpha()`
- `s.isdigit()`
- `s.isspace()`
- `s.islower()`
- `s.isupper()`
- `s.istitle()`
- `s.endswith(suffix)`
- `s.startswith(prefix)`

Finding things in strings:

- `s.count(substring)`
- `s.find(substring)`
- `s.index(substring)`
- `s.rfind(substring)`
- `s.rindex(substring)`

Changing strings. Remember that strings are immutable so to make a change "stick" you have to do, e.g. `s = s.title()`.

- `s.swapcase()`
- `s.upper()`
- `s.lower()`
- `s.title()`
- `s.capitalize()`
- `s.center()`
- `s.ljust()`
- `s.rjust()`
- `s.strip()`
- `s.lstrip(chars)`
- `s.rstrip(chars)`

String to list:

- `list = s.split(list)`

List to string:

- `s.join(list)` where `s` is the string to join the elements of list with.

Assignment

Use = to assign a name to a value, e.g.

```
distance = 48.1, name = "Tim Topper".
```

Remember that the name has to be on the left hand side of the =, i.e. `48.1 = distance` is an error.

print

Use `print` to display stored values.

```
print list
```

Displays the value of each item in the list. Puts a space between each pair of values. Example:

```
print "The answer is", 5 + 2, "."
```

displays:

```
The answer is 7 .
```

Appending a comma to the end of a print statement holds the current output line open, e.g. the code

```
print "The answer is",
print 5 + 2, "."
```

displays

```
The answer is 7 .
```

on a single line.

For more control over output appearance embed formatting codes into output strings. See section [2.2.6.2 String Formatting Operations](#) of the Python Library Reference for the gory details.

Getting Input

Use `input` to get numerical data from the user,

```
input( string )
```

and `raw_input` to get string data.

Both display `string` (if given) and then read a line of input, by default from the keyboard. The difference is that `raw_input` just returns the string, while `input` evaluates it as a Python expression and returns the result. Example:

```
distance = input(" Enter the distance in miles: " )
name = raw_input(" What is your name? " )
```

N.B. the spaces before the second " in each case.

if

Use `if` to execute one block of code or another, but not both.

```
if test:
    statements
elif test:
    statements
else:
    statements
```

N.B. the `elif` and `else` statements are optional as shown in the first two examples below.

Examples:

```
if x < 0: print x, "is negative"
if flip == 1:
    print "You got heads"
else:
    print "You got tails"
if num < 0:
    print "The number", num, "is negative."
elif num == 0:
    print "The number", num, "is neither positive
nor negative."
else:
    print "The number", num, "is positive."
while
```

Use `while` to execute a block of code multiple times.

```
while test:
    statements
```

Examples:

```
x = 1
while x < 10
    print x
    x = x + 1
num = input( "Enter a number between 1 and 100:
" )
while num < 1 or num > 100:
    print "Oops, your input value (", num, ") is
out of range."
    num = input( "Be sure to enter a value between
1 and 100: " )
```

Play again? Repeating a program

```
again = "y"
while again == "y" or again == "Y" or again ==
"yes" or again == "Yes":

    #
    # Put the body of your program here
    #

    again = raw_input( "Play again (y/n)? " )

print "Thanks for playing"
```

Lists

Unlike many languages Python provides a built-in list type. A list constant is just a list of items separated by commas and placed inside square brackets, e.g. ["Tim", 42, "Molly"].

Python provides for a wealth of list operations (complete list in [reference manual](#)):

- `list1 + list2` : concatenates `list1` and `list2`
- `list[i]` : access element number `i` in `list`.
- `len(list)` : returns the number of elements in `list`
- `del list[i]` : deletes element number `i` from `list`
- `list.append(value)` : appends `value` to `list`
- `list.sort()` : sorts the elements in `list`
- `list.reverse()` : reverses the order of the elements in `list`
- `list.index(value)` : returns the position of the first occurrence of `value` in `list`
- `list.insert(i, value)` : inserts `value` into `list` at position `i`
- `list.count(value)` : returns a count of the number of times `value` occurs in `list`
- `list.remove(value)` : deletes the first occurrence of `value` in `list`
- `list.pop()` : deletes and returns the last value in `list`
- `value in list` : is `True` if `value` occurs in `list` and `False` otherwise

N.B. the elements in lists are numbered from 0, not 1.

Text file processing

To read from a file a line at a time:

```
infilename = raw_input( "Name of file to read
from: " )
infile = open( infilename, "r" )
for line in infile:
    # Do stuff with line.
    # Remember that line is a string even if it
looks like a number,
    # e.g. num = int( line )
infile.close()
```

There's more than this of course. You can also read the entire file into a string in one fell swoop using `infile.read()`, read the entire file into a list of strings (one per line in the file) using `infile.readlines()`, or read a certain number of bytes using `infile.read(N)` where `N` gives the number of bytes to read.

To write to a file:

```
outfilename = raw_input( "Name of file to write
to: " )
outfile = open( outfilename, "w" )
print >> outfile, ...
outfile.close()
```

For more see the [Python library reference on File Objects](#).

Dictionaries

Python provides a built-in lookup table type it calls a dictionary (often called hash tables in other languages).

A dictionary constant consists of a series of key-value pairs enclosed by curly braces, e.g. `d = { 'Tim' : 775, 'Brian' : 869 }`. This creates a dictionary we can visualize as:

Key	Value
'Tim'	→ 775
'Brian'	→ 869

Common dictionary operations include:

- `d['Tim']` Accessing an element.
- `d['A-S'] = 770` Modifying or inserting a value.
- `d.has_key('Brian')` Checking to see if there is a value for a particular key.
- `d.keys()` Get a list of all the keys in the dictionary. Often used for iterating through the entries in the dictionary.
- `d.values()` Get a list of all the values that occur in the dictionary.
- `del(d['Tim'])` Delete an entry in the dictionary.
- `d.clear()` Delete all the entries in a dictionary.